



DRILL #30 (Ø0.128 REF)
C'SINK Ø0.230X100°
TYP 22 PLACES

Ø0.386 +0.005/-0.000
HOLE TO BE ALIGNED
WITHIN ±0.001 OF HOLE
ON OTHER SIDE OF CUFF,
TYP 6 PLACES

- NOTES:**
- 1) MATERIAL: 7075-T6/T6511 SEAMLESS TUBE (VV-T-700/7 OR QQ-A-225/9 OR QQ-A-200/11)
(CAN MAKE FROM D6006, D6008, OR D6009)
 - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: NONE
 - 7) WEIGHT: 0.50 lbs

D3660-1 CUFF

B	ADD Ø0.128 & Ø0.386 HOLES (B8)	CP	08.03.03
A	NEW ISSUE	CP	07.07.07
REV.	DESCRIPTION	BY	DATE
DESIGN		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED		DRAWING NO.	REV. B
MFG. APPR.		D3660	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		CUFF	NTS
DATE	08.03.03	COPYRIGHT © 2007 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	